

## Metal Screws

### Self-Drilling Fiber-Cement Screw


#### Common Application:

Fasten fiber cement through furring strips to steel studs

#### Features:

- Wafer head, square drive, self-countersinking nibs under the head.
- Threaded to within  $\frac{5}{16}$ " of top of head.
- #3 drill point.
- #2 square drive (replacement bit model BIT2S-2; see p. 111 for more information).
- Type 410 stainless steel is coated for additional corrosion protection.
- Type 410 stainless steel can be hardened through heat treatment, giving it the ability to drill through metal. It does not offer the same level of corrosion resistance of either Type 316 or 305 stainless steel.
- **Warning:** Hardened stainless-steel fasteners should not be used with steel framing in environments with high humidity, condensation or other moisture that will be present at the dissimilar-metal interface.

For more information on drilling thickness capacities and drill speed recommendations see pp. 27-28.



#### Type 410 Stainless Steel\*

Size	Length (in.)	Threads Per Inch	Head Diameter (in.)	Carton Quantity	Model No.
#8	1 $\frac{5}{8}$	18	0.39	100	F08T162WDC
#8	1 $\frac{5}{8}$	18	0.39	1,000	F08T162WDM
#8	1 $\frac{5}{8}$	18	0.39	3,000	F08T162WDB
#8	2 $\frac{1}{4}$	18	0.39	100	F08T225WDC
#8	2 $\frac{1}{4}$	18	0.39	1,000	F08T225WDM
#8	2 $\frac{1}{4}$	18	0.39	2,500	F08T225WDB

\* These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.